

PU-D20 Concrete System & DLP Floating Floor (A60)

Product description


The build-up consists of a vibration damped floor in combination with a floating floor. The vibration damped floor construction is a sandwich floor construction consisting of minimum 10 mm BH 3000 as a constrained top layer applied on top of minimum 1 mm visco elastic damping layer type PU-D20.

On top of the PU-D20 Concrete System a floating floor is applied. The floating floor consists of minimum 50 mm SeaRox SL436. The top layer consists of 3 mm steel plate, 1 mm PU-D20 and 2 mm steel plate.

By using these two systems together in one build-up it will be possible to get a better reduction of both noise and vibration.

Technical description

Density	PU-D20 approx. 1,35 kg/mm/m ² BH 3000 approx. 1,6 kg/mm/m ² SeaRox SL436-50 mm approx. 0,14 kg/mm/m ² Steel plate approx. 8 kg/mm/m ²
Thickness of build-up	Minimum 67 mm
Weight of build-up	Approx. 66 kg/m ²



The information and in particular, the recommendations relating to the application and end use of DMS products, are given in good faith based on our current knowledge and experience. The information and recommendations are given without warranty of any kind and does not lead to any further liability for DMS, besides what is stated in the sales agreement. It is the buyer or end-user's responsibility to investigate or in other way make sure that DMS product suitable for the intended use and further are stored, handled and applied in accordance with stated directions. All orders are delivered and accepted in accordance with our general conditions of sale

For additional technical information, please contact our technical department.