

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

DMS Tile Fix

Product no.

-

REACH registration number

Not applicable

Other means of identification

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Thin joint adhesive or glue

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

DMS A/S
Randersvej 12
6700 Esbjerg
Denmark
Phone: +45 7023 2343
Fax: +45 7023 4342

Contact person

Jan Laursen

E-mail

jl@dms-as.com

SDS date

2016.12.01

SDS Version

1.0

1.4. Emergency telephone number

Use your national or local emergency number
See section 4 "First aid measures"

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Skin Irrit. 2, Eye Dam. 1, STOT SE 3 // H335, H318, H315
See full text of H/R-phrases in section 2.2.

DPD/DSD Classification

Irritant. (Xi).
Irritating to respiratory system and skin.(R37/38). Risk of serious damage to eyes.(R41).

According to EC-Regulation 1907/2006 (REACH)

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger!

Hazard statement(s)

Causes skin irritation. (H315)
 Causes serious eye damage. (H318)
 May cause respiratory irritation. (H335)

Identity of the substances primarily responsible for the major health hazards

Cement, portland, calcium diformate

Safety statement(s)	General	If medical advice is needed, have product container or label at hand. (P101) Keep out of reach of children. (P102)
	Prevention	Wear protective gloves/protective clothing/eye protection/face protection. (P280)
	Response	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
	Storage	Store locked up. (P405)
	Disposal	Dispose of contents/container to an approved waste disposal plant. (P501)

2.3. Other hazards

The product is corrosive when mixed with water.

Additional labelling

The content of water-soluble chromate is less than 2 ppm in dry storage up to 12 months from production date. If stored under moist conditions, the chromate reduction can be impaired.

Additional warnings

-

VOC

-

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances

NAME: Cement, portland
 IDENTIFICATION NOS.: CAS-no: 65997-15-1 EC-no: 266-043-4
 CONTENT: 25-40%
 DSD CLASSIFICATION: Xi;R41 R37/38
 CLP CLASSIFICATION: STOT SE 3, Skin Irrit. 2, Eye Dam. 1
 H315, H318, H335

NAME: calcium diformate
 IDENTIFICATION NOS.: CAS-no: 544-17-2 EC-no: 208-863-7
 CONTENT: <1%
 DSD CLASSIFICATION: Xi;R36/38
 CLP CLASSIFICATION: Eye Dam. 1
 H318

(*) See full text of H/R-phrases in chapter 16. Occupational limits are listed in section 8, if these are available.

Other informations

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

Inhalation

Get the person into fresh air and stay with them.

Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses. Flush eyes with plenty of water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. Contact a doctor at once.

Ingestion

Give the person plenty to drink and stay with the person. If the person feels unwell, contact a doctor immediately and take this safety data sheet or the label from the product with you. Do not induce vomiting unless recommended by the doctor. Hold head facing down so that no vomit runs back into the mouth and throat.

Burns

Rinse with water until the pain stops and continue for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

4.3. Indication of any immediate medical attention and special treatment needed

No special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Some metal oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours from waste material. Avoid direct contact with spilled substances.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Sweep up spills carefully. Use water sprays or ventilated evacuation systems to prevent dust. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

6.4. Reference to other sections

See section on "Disposal" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, consumption of food or liquid, and storage of tobacco, food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection. Avoid direct contact with the product.

7.2. Conditions for safe storage, including any incompatibilities

Store dry.

Storage temperature

NA

7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

Quartz (EH40, 2011)

Long-term exposure limit (8-hour TWA reference period): - ppm | 0,1 mg/m³

Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

Cement, portland (EH40/2005, 2011)

Long-term exposure limit (8-hour TWA reference period): - ppm | 10 mg/m³

Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

Quartz (SiO₂) (EH40, 2011)

Long-term exposure limit (8-hour TWA reference period): - ppm | 0,1 mg/m³

Short-term exposure limit (15-minute reference period): - ppm | - mg/m³

DNEL / PNEC

No data available.

8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

General recommendations

Smoking, consumption of food or liquid, and storage of tobacco, food or liquid, are not allowed in the workroom.

Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

Exposure limits

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

According to EC-Regulation 1907/2006 (REACH)

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible collect spillage during work.

Individual protection measures, such as personal protective equipment



Generally

Only CE-marked personal protection equipment should be used.

Respiratory Equipment

If the ventilation at the work place is not sufficient, use a half or whole mask with an appropriate filter or an air-supplied respiratory protector. The choice depends on the concrete work situation and how long you will be using the product.

Skin protection

Special work clothing should be used. When working with this product for a long period of time, use a protective suit.

Hand protection

Use protective gloves. The concrete work situation is not known. Contact the suppliers of the gloves for help on the glove type. Please note that elastic gloves stretch when used. The thickness of the gloves, and therefore their penetration time, will be reduced. Moreover, the temperature of the glove in use is about 35°C, while the standard test, EN 374-3, is done at 23°C. The penetration time is therefore reduced by a factor of 3.

Eye protection

Use face shield. Use safety glasses with a side shield as an alternative.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Colour	Odour	pH	Viscosity	Density (g/cm ³)
Solid	NA	NA	-	-	-

Phase changes

Melting point (°C)	Boiling point (°C)	Vapour pressure (mm Hg)
-	-	-

Data on fire and explosion hazards

Flashpoint (°C)	Ignition (°C)	Self ignition (°C)
-	-	-

Explosion limits (Vol %)	Oxidizing properties
-	-

Solubility

Solubility in water	n-octanol/water coefficient
Soluble	-

9.2. Other information

Solubility in fat	Additional information
-	N/A

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

10.3. Possibility of hazardous reactions

No special

According to EC-Regulation 1907/2006 (REACH)

10.4. Conditions to avoid

No special

10.5. Incompatible materials

Strong acids, strong bases, strong oxidising agents, and strong catabolic agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance	Species	Test	Route of exposure	Result
No data available.				

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

No data available. **Germ**

cell mutagenicity No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Long term effects

Irritation effects: This product contains substances which cause irritation to skin and eyes, or when inhaled. Contact with locally irritative substances can cause the area of contact to be more prone to absorb damaging substances such as allergens.

SECTION 12: Ecological information

12.1. Toxicity

Substance	Species	Test	Test duration	Result
No data available.				

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
No data available.			

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BFC
No data available.			

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No special

According to EC-Regulation 1907/2006 (REACH)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The product is covered by the regulations on dangerous waste.

Waste

EWC code

-

Specific labelling

-

Contaminated packing

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

SECTION 14: Transport information

Not listed as dangerous goods under ADR and IMDG regulations.

14.1 – 14.4

ADR/RID

14.1. UN
number

14.2. UN proper shipping
name

14.3. Transport hazard
class(es)

14.4. Packing
group

Notes

IMDG

UN-no.

Proper Shipping Name

Class

PG*

EmS

MP**

Hazardous
constituent

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 must not be exposed to this product cf. Council Directive 94/33/EC. For exceptions, see the Danish Working Environment Authority's Executive Order No. 239 of 6 April 2005.

Demands for specific education

-

Additional information

-

15.2. Chemical safety assessment

No

SECTION 16: Other information'

Sources

EC regulation 1907/2006 (REACH)

Directive 2000/532/EC

EC Regulation 1272/2008 (CLP)

Full text of H/R-phrases as mentioned in section 3

R41 - Risk of serious damage to eyes.

R36/38 - Irritating to eyes and skin.

R37/38 - Irritating to respiratory system and skin.

According to EC-Regulation 1907/2006 (REACH)

H315 - Causes skin irritation.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.

The full text of identified uses as mentioned in section 1

Other symbols mentioned in section 2

-

Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.
A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

The safety data sheet is validated by

PIPE/CHYMEIA

**Date of last essential change
(First cipher in SDS version)**

-

**Date of last minor change
(Last cipher in SDS version)**

-