

# Safety Data Sheet

## Efadeck Clear 0454

Replaces date: 06-07-2016

Revision date: 25-10-2016

### SECTION 1: Identification of the substance/preparation and of the company/undertaking

#### 1.1. Product identifier

**Trade name:** Efadeck Clear 0454

#### Article no

Article no	Description
0454	

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended uses:** Painting of concrete.

**Inadvisable uses:** The product is recommended for only the above described uses.

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

**Company:** Esbjerg Farve- & Lakfabrik A/S

**Address:** Energivej 13

**Zip code:** DK-6700 Esbjerg

**Country:** DENMARK

**E-mail:** info@esbjergpaints.dk

**Phone:** 0045 75 12 86 00

**Fax:** 0045 75 45 33 68

**Homepage:** www.esbjergpaints.dk

#### 1.4. Emergency Telephone Number

GB: +44 1215074123 (Advice and guidance ) (Around the clock)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**CLP-classification:** Flam. Liq. 3;H226 Skin Irrit. 2;H315 Skin Sens. 1;H317 Eye Irrit. 2;H319 Acute Tox. 4;H332 Resp. Sens. 1B;H334 STOT SE 3;H335 STOT SE 3;H336 Carc. 2;H351 STOT RE 2;H373 Aquatic Chronic 2;H411

**Most serious harmful effects:** Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Pictograms

# Safety Data Sheet

## Efadeck Clear 0454

Replaces date: 06-07-2016

Revision date: 25-10-2016



**Signal word:** Danger

### Contains

**Substance:** Solvent naphtha (petroleum), light arom.; Aromatic polyisocyanate prepolymer; 4,4'-methylenediphenyl diisocyanate; MDI, oligomeric; o-(p-isocyanatobenzyl)phenyl isocyanate

### H-phrases

H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

### P-phrases

P273 Avoid release to the environment.  
P281 Use personal protective equipment as required.  
P285 In case of inadequate ventilation wear respiratory protection.  
P302/352 IF ON SKIN: Wash with plenty of soap and water.  
P304/341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305/351/338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P342/311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.  
P280 Wear protective gloves/protective clothing/eye protection.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing vapours.

### Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

### 2.3. Other hazards

The product does not contain any PBT or vPvB substances.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Substance	CAS number	EC No	REACH Reg. No.	Concentration	Notes	CLP-classification
Solvent naphtha (petroleum), light arom.	64742-95-6	265-199-0	01-2119455851-35	25 - 50%		Flam. Liq. 3;H226 Asp. Tox. 1;H304 STOT SE 3;H335 STOT SE 3;H336 Aquatic Chronic 2;H411
Xylene	1330-20-7	215-535-7	01-2119488216-32	10 - 25%		Flam. Liq. 3;H226 Acute Tox. 4;H312 Skin Irrit. 2;H315 Acute Tox. 4;H332

# Safety Data Sheet

## Efadeck Clear 0454

Replaces date: 06-07-2016

Revision date: 25-10-2016

4,4'-methylenediphenyl diisocyanate	101-68-8	202-966-0	01-2119457014-47	10 - 25%	Skin Irrit. 2;H315 Skin Sens. 1;H317 Eye Irrit. 2;H319 Acute Tox. 4;H332 Resp. Sens. 1;H334 STOT SE 3;H335 Carc. 2;H351 STOT RE 2;H373
Aromatic polyisocyanate prepolymer	67815-87-6			20 - 25%	Skin Irrit. 2;H315 Skin Sens. 1;H317 Eye Irrit. 2;H319 Acute Tox. 4;H332 Resp. Sens. 1;H334 STOT SE 3;H335 STOT RE 2;H373
ethylbenzene	100-41-4	202-849-4		2.5 - 10%	Flam. Liq. 2;H225 Asp. Tox. 1;H304 Acute Tox. 4;H332 STOT RE 2;H373
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	227-534-9	01-2119480143-45	2.5 - 10%	Skin Irrit. 2;H315 Skin Sens. 1;H317 Eye Irrit. 2;H319 Acute Tox. 4;H332 Resp. Sens. 1;H334 STOT SE 3;H335 Carc. 2;H351 STOT RE 2;H373
MDI, oligomeric	32055-14-4	500-079-6	01-2119457024-46	5 - 10%	Skin Irrit. 2;H315 Skin Sens. 1;H317 Eye Irrit. 2;H319 Acute Tox. 4;H332 Resp. Sens. 1;H334 STOT SE 3;H335 Carc. 2;H351 STOT RE 2;H373

Please see section 16 for the full text of H-phrases.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- Inhalation:** If patient feels unwell move to fresh air and keep under surveillance. If the victim is unconscious, ascertain whether the victim is breathing. If breathing has stopped, apply artificial respiration. If the victim is unconscious but breathing, place in the recovery position and keep warm with blankets. Call for medical attention or ambulance.
- Ingestion:** Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention immediately!
- Skin contact:** Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above. Do not use solvents.
- Eye contact:** Flush immediately with water (preferably using eye wash equipment) for at least 5 minutes. Open eye wide. Remove any contact lenses. Seek medical advice.
- Burns:** Flush with plenty of water until pain ceases. Whilst flushing with water, remove all loose clothing from area of burns. If medical treatment is necessary, continue rinsing until a doctor takes over the treatment.
- General:** If in doubt, seek medical advice. Also see para. 1

#### 4.2. Most important symptoms and effects, both acute and delayed

Pain in the eyes, redness, tears, swollen eyelids, itching Headache, dizziness, drowsiness and nausea. Sensitization of the skin and respiratory tract.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Depending on the extent of exposure, a prolonged medical observation may be necessary.

### SECTION 5: Fire-fighting measures

# Safety Data Sheet

## Efadeck Clear 0454

Replaces date: 06-07-2016

Revision date: 25-10-2016

### 5.1. Extinguishing media

**Suitable extinguishing media:** Fire can be extinguished with carbon dioxide, powder, foam or water spray.

**Unsuitable extinguishing media:** Do not use a direct water jet that could spread the fire.

### 5.2. Special hazards arising from the substance or mixture

Fire will produce carbon monoxide, carbon dioxide, nitrogen oxides, isocyanate vapors and traces of hydrogen cyanide.

### 5.3. Advice for fire-fighters

Cool closed containers with water. Fire will produce a thick black smoke. Products of combustion are harmful and respiratory protection is required.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel:** Avoid inhalation of vapours. Avoid all skin contact. See protection measures in item 7 and 8. Remove all ignition sources and ensure sufficient ventilation.

**For emergency responders:** Use nitrile protection gloves and self-contained breathing apparatus.

### 6.2. Environmental precautions

Notify proper authorities in case of contamination of soil or aquatic environment or discharge to drains.

### 6.3. Methods and material for containment and cleaning up

Prevent major quantities of spillage from being discharged into the sewage system or water by banking the spillage with sand or the like and collecting it. Clean the contaminated area with a suitable cleaning agent, but do not use solvent.

### 6.4. Reference to other sections

Also see item 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

The product may be charged electrostatically. Always use underground wire when transferring from one container to another. Personnel should wear antistatic shoes and clothing. Floors should be conductive. Do not use tools which may produce sparks. Avoid contact with eyes and skin. Avoid inhaling vapors and spray mists. Vapors may form explosive mixtures with air. Prevent the formation of flammable or explosive mixtures. Do not use this material near naked flames or any other ignition source. Electrical installations must be protected according to regulations.

### 7.2. Conditions for safe storage, including any incompatibilities

The product must be kept away from children. Store in a tightly closed container and in accordance with the current regulations in a dry and well-ventilated place away from food. Keep away from ignition sources, oxidizing agents and strong acidic and basic substances. No smoking and use of open fire. No admittance to unauthorized persons. Opened containers must be carefully closed and stored upright to prevent any leakage.

### 7.3. Specific end use(s)

Applications is mentioned in item 1.2.

**Other Information:** Smoking and the consumption of food and drink are not permitted in work rooms. Personal protective equipment: Refer to section 8.

# Safety Data Sheet

## Efadeck Clear 0454

Replaces date: 06-07-2016

Revision date: 25-10-2016

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limit

Substance name	Time period	ppm	mg/m3	Comment	Remarks
Xylene	8h	50	220		BMGV, Sk
Xylene	15m	100	441		BMGV, Sk
ethylbenzene	8h	100	441		Sk
ethylbenzene	15m	125	552		Sk

BMGV = Biological monitoring may be appropriate and Biological Monitoring Guidance Value is listed in Table 3 (Occupational Exposure Limits)

Sk = Can be absorbed through skin

**Legal basis:** EH40/2005 Workplace exposure limits incl. supplement from October 2007.

##### PNEC

Xylene				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
Freshwater	0,327 mg/l			
Marine water	0,327 mg/l			
Freshwater - sediment	12,46 mg/kg			
Marine water - sediment	12,46 mg/kg			
Soil	2,31 mg/kg			

4,4'-methylenediphenyl diisocyanate				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
Freshwater	> 1 mg/l			
Marine water	> 0,1 mg/l			
Soil	> 1 mg/kg			

MDI, oligomeric				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
Marine water	> 0,1 mg/l			
Soil	> 1 mg/kg			
Freshwater	> 1 mg/l			

o-(p-isocyanatobenzyl)phenyl isocyanate				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
Freshwater	> 1 mg/l			
Marine water	> 0,1 mg/l			
Soil	> 1 mg/kg			

ethylbenzene				
Exposure	Value	Assessment Factor	Extrapolation Method	Note
Freshwater	0,1 mg/l			
Marine water	0,01 mg/l			
Freshwater - sediment	13,7 mg/kg			
Soil	2,68 mg/kg			

##### DNEL - workers

Solvent naphtha (petroleum), light arom.					
Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal	25 mg/kg bw/day	Long-term exposure		Systemic effects	

# Safety Data Sheet

## Efadeck Clear 0454

Replaces date: 06-07-2016

Revision date: 25-10-2016

Inhalation	100 mg/m3	Long-term exposure		Systemic effects	
------------	-----------	--------------------	--	------------------	--

### Xylene

Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Inhalation	289 mg/m3	Acute / short-term exposure		Systemic effects	
Inhalation	289 mg/m3	Acute / short-term exposure		Local effects	
Dermal	180 mg/kg bw/day	Long-term exposure		Systemic effects	
Inhalation	77 mg/m3	Long-term exposure		Systemic effects	

### 4,4'-methylenediphenyl diisocyanate

Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal	50 mg/kg bw/day	Acute / short-term exposure		Systemic effects	
Inhalation	0,1 mg/m3	Acute / short-term exposure		Systemic effects	
Dermal	28,7 mg/cm2	Acute / short-term exposure		Local effects	
Inhalation	0,1 mg/m3	Acute / short-term exposure		Local effects	
Inhalation	0,05 mg/m3	Long-term exposure		Systemic effects	
Inhalation	0,05 mg/m3	Long-term exposure		Local effects	

### MDI, oligomeric

Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal	50 mg/kg bw/day	Acute / short-term exposure		Systemic effects	
Inhalation	0,1 mg/m3	Acute / short-term exposure		Systemic effects	
Dermal	28,7 mg/cm2	Acute / short-term exposure		Local effects	
Inhalation	0,1 mg/m3	Acute / short-term exposure		Local effects	
Inhalation	0,05 mg/m3	Long-term exposure		Systemic effects	
Inhalation	0,05 mg/m3	Long-term exposure		Local effects	

### o-(p-isocyanatobenzyl)phenyl isocyanate

Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal	50 mg/kg bw/day	Acute / short-term exposure		Systemic effects	
Inhalation	0,1 mg/m3	Acute / short-term exposure		Systemic effects	
Dermal	28,7 mg/cm2	Acute / short-term exposure		Local effects	
Inhalation	0,1 mg/m3	Acute / short-term exposure		Local effects	
Inhalation	0,05 mg/m3	Long-term exposure		Systemic effects	
Inhalation	0,05 mg/m3	Long-term exposure		Local effects	

### ethylbenzene

Exposure	Value	Assessment Factor	Dose Descriptor	Main Impact Parameter	Note
Dermal	180 mg/kg bw/day	Long-term exposure		Systemic effects	
Inhalation	77 mg/m3	Long-term exposure		Systemic effects	

# Safety Data Sheet

## Efadeck Clear 0454

Replaces date: 06-07-2016

Revision date: 25-10-2016

Inhalation	293 mg/m <sup>3</sup>	Acute / short-term exposure		Local effects	
------------	-----------------------	-----------------------------	--	---------------	--

**Biological threshold values:** See above.

**Other Information:** See above.

### 8.2. Exposure controls

**Appropriate engineering controls:** All work must be planned with a view to limit the breathing of fumes and the exposure to the skin. Work under effective process ventilation (e.g. local exhaust ventilation). If this is not possible, use respiratory protection.

**Personal protective equipment, eye/face protection:** Use suitable protective goggles or full face mask for protection against splashes.

**Personal protective equipment, skin protection:** If possible, wear special work clothes. When spraying wear coveralls.

**Personal protective equipment, hand protection:** Use nitrile protection gloves. A 15-mil thickness glove provides a one-hour breakthrough-time. Follow the glove manufacturer's recommendations on use and replacement.

**Personal protective equipment, respiratory protection:** Use compressed-air full face mask.

**Environmental exposure controls:** It must be ensured that local regulations for discharge are met.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Parameter	Value/unit
State	Liquid
Colour	Yellowish
Odour	Odour of organic solvent.
Solubility	Soluble in: Organic solvents.
Explosive properties	See explosive limits
Oxidising properties	No information available

Parameter	Value/unit	Remarks
pH (solution for use)	No data	
pH (concentrate)	No data	
Melting point	No data	
Freezing point	No data	
Initial boiling point and boiling range	No data	
Flash Point	25 °C	
Evaporation rate	No data	
Flammability (solid, gas)	No data	
Flammability limits	No data	
Explosion limits	1 - 8	
Vapour pressure	No data	
Vapour density	No data	
Relative density	No data	
Partition coefficient n-octanol/water	No data	
Auto-ignition temperature	No data	
Decomposition temperature	No data	
Viscosity	> 20.5 mm <sup>2</sup> /s /40°C	
Odour threshold	No data	

# Safety Data Sheet

## Efadeck Clear 0454

Replaces date: 06-07-2016

Revision date: 25-10-2016

### 9.2 Other information

Parameter	Value/unit	Remarks
Density	0.93 g/ml	
Fire class	II-1	
Weight % organic solvents	60	
VOC	558g/l	

**Other Information:** Solubility in water: Insoluble in water. Fat solubility: irrelevant

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

See below.

### 10.2. Chemical stability

Stable under recommended storage and handling conditions.  
Curing time: 3 days at 20 ° C.

### 10.3. Possibility of hazardous reactions

Ignitable at temperatures above the flash point. The fumes can ignite by e.g. a spark, a warm surface or a glow. The fumes can mix to explosive mixtures with air. At room temperature the fumes are more heavily than air and can spread along the floor.

### 10.4. Conditions to avoid

Stable at normal temperature. When exposed to high temperatures, toxic decomposition products may be formed.

### 10.5. Incompatible materials

To prevent heat-generating reactions, keep the product away from oxidizing agents and strong acidic and basic substances. Isocyanates react violently with water producing heat.

### 10.6. Hazardous decomposition products

carbon monoxide. Nitric oxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

#### Solvent naphtha (petroleum), light arom.

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		3592mg/kg		OECD 401	

#### Xylene

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		> 2000mg/kg			

#### o-(p-isocyanatobenzyl)phenyl isocyanate

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LD50		> 2000mg/kg		84/449/EEC, B. 1	



# Safety Data Sheet

## Efadeck Clear 0454

Replaces date: 06-07-2016

Revision date: 25-10-2016

Ingestion of large quantities may cause gastrointestinal disorders.

### Acute toxicity - dermal

#### Solvent naphtha (petroleum), light arom.

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		3160mg/kg		OECD 402	

#### Aromatic polyisocyanate prepolymer

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		> 9400mg/kg		OECD 402	

#### Xylene

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		3200 mg/kg			

#### 4,4'-methylenediphenyl diisocyanate

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		> 9400mg/kg		OECD 402	

#### o-(p-isocyanatobenzyl)phenyl isocyanate

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rabbit	LD50		> 9400mg/kg		OECD 402	

Organic solvents have a degreasing effect on the skin. Organic solvents may be absorbed through skin. Isocyanates may cause allergic (contact) eczema. Remove contamination immediately by skin contact.

### Acute toxicity - inhalation

#### Solvent naphtha (petroleum), light arom.

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LC50		> 6193mg/l		OECD 403	

#### Xylene

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LC50	4 h	21.7 mg/l			

#### 4,4'-methylenediphenyl diisocyanate

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LC50	4 h	0.368mg/l		OECD 403	

#### o-(p-isocyanatobenzyl)phenyl isocyanate

Organism	Test Type	Exposure time	Value	Conclusion	Test method	Source
Rat	LC50	4 h	0.387mg/l			

Products containing isocyanates can cause acute irritation, coughing and breathing difficulties. In the longer term inhalation cause asthma, for sensitizing people even when exposed to low concentrations. Repeated inhalation may cause permanent damage to the respiratory passages. Inhalation of vapors may cause symptoms of poisoning such as memory and concentration difficulties, abnormal tiredness, irritability and, in extreme cases, unconsciousness. Prolonged and repeated inhalation of high concentrations may cause damage to liver, kidneys, brain and nervous system.

**Skin corrosion/irritation:** Prolonged or repeated skin contact will degrease skin and may cause irritation.

**Serious eye damage/eye irritation:** Splashing into eyes may cause smarting/irritation.

# Safety Data Sheet

## Efadeck Clear 0454

Replaces date: 06-07-2016

Revision date: 25-10-2016

<b>Germ cell mutagenicity:</b>	Would not be expected germ cell mutagen
<b>Carcinogenic properties:</b>	Contains Ethylbenzene and Diphenylmethane classified Carc 3; possibility of a carcinogenic effect.
<b>Reproductive toxicity:</b>	Would not be expected to be a reproductive toxicant.
<b>Single STOT exposure:</b>	May cause respiratory irritation. May cause drowsiness or dizziness.
<b>Repeated STOT exposure:</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard:</b>	Test data are not available.

### SECTION 12: Ecological information

#### 12.1. Toxicity

##### Solvent naphtha (petroleum), light arom.

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Acute Daphnia		48 h	EC50	32mg/l			

##### Aromatic polyisocyanate prepolymer

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Acute daphnia	Daphnia magna	21 d	NOEC	> 10mg/l		OECD 202	

##### Xylene

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Acute algae	Pseudokirchneriella subcapitata	72 h	EC50	2.2mg/l		OECD 201	
Acute Daphnia	Daphnia magna	24 h	IC50	1mg/l		OECD 202	
Acute fish	Oncorhynchus mykiss	96 h	LC50	2.6mg/l		OECD 203	

##### 4,4'-methylenediphenyl diisocyanate

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Acute Daphnia	Daphnia magna	21 d	NOEC	> 10mg/l		#Not translated#	

##### MDI, oligomeric

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Acute fish	#Not translated#	96 h	LC50	> 1000mg/l		#Not translated#	
Acute algae	#Not translated#	72 h	EC50	> 1640mg/l		#Not translated#	
Acute Daphnia	#Not translated#	21 d	NOEC	> 10mg/l		#Not translated#	

##### ethylbenzene

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
Acute daphnia	Daphnia magna	48 h	EC50	290mg/l			
Acute fish	Cyprinodon variegatus	96 h	LC50	88mg/l			

# Safety Data Sheet

## Efadeck Clear 0454

Replaces date: 06-07-2016

Revision date: 25-10-2016

### 12.2. Persistence and degradability

#### MDI, oligomeric

Organism	Species	Exposure time	Test Type	Value	Conclusion	Test method	Source
		28 d		0 %		#Not translated#	

No information available

### 12.3. Bioaccumulative potential

No information available

### 12.4. Mobility in soil

The product is insoluble in water and will spread out on the surface.

### 12.5. Results of PBT and vPvB assessment

No information available

### 12.6. Other adverse effects

No information available

#### Other Information

Do not dispose of this product in drains, watercourses, or on the ground. This product is classified as hazardous to the environment according to the calculation method. Please see par. 2 and 3 for further information.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Avoid discharge to drain or surface water.

Product residues are classified as chemical waste.

**Category of waste:** Waste-code: 08 01 11

## SECTION 14: Transport information

### Land transport (ADR/RID)

<b>14.1. UN-No.:</b>	1263	<b>14.4. Packing group:</b>	III
<b>14.2. UN proper shipping name:</b>	PAINT RELATED MATERIAL	<b>14.5. Environmental hazards:</b>	
<b>14.3. Transport hazard class(es):</b>	3		
<b>Hazard label(s):</b>	3		
<b>Hazard identification number:</b>	30	<b>Tunnel restriction code:</b>	D/E
<b>Other Information:</b>			

### Inland water ways transport (ADN)

<b>14.1. UN-No.:</b>	1263	<b>14.4. Packing group:</b>	III
<b>14.2. UN proper shipping name:</b>	PAINT RELATED MATERIAL	<b>14.5. Environmental hazards:</b>	
<b>14.3. Transport hazard class(es):</b>	3		

# Safety Data Sheet

## Efadeck Clear 0454

Replaces date: 06-07-2016

Revision date: 25-10-2016

**Hazard label(s):** 3  
**Environmentally hazardous in tank vessels:**

**Other Information:**

### Sea transport (IMDG)

<b>14.1. UN-No.:</b>	1263	<b>14.4. Packing group:</b>	III
<b>14.2. UN proper shipping name:</b>	PAINT RELATED MATERIAL	<b>14.5. Environmental hazards:</b>	
<b>14.3. Transport hazard class(es):</b>	3	<b>Environmental Hazardous Substance Name(s):</b>	
<b>Hazard label(s):</b>	3		
<b>EmS:</b>	F-E, S-E	<b>IMDG Code segregation group:</b>	- None -

**Other Information:**

### Air transport (ICAO-TI / IATA-DGR)

<b>14.1. UN-No.:</b>	1263	<b>14.4. Packing group:</b>	III
<b>14.2. UN proper shipping name:</b>	PAINT RELATED MATERIAL	<b>14.5. Environmental hazards:</b>	
<b>14.3. Transport hazard class(es):</b>	3		
<b>Hazard label(s):</b>	3	<b>Other Information:</b>	

### 14.6. Special precautions for user

Irrelevant.

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC code

Irrelevant.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Special Provisions:**

**Authorisations / limitations:**

### 15.2. Chemical Safety Assessment

REACH Reg. No.	Substance name
01-2119457024-46	MDI, oligomeric

**Other Information:** Chemical safety assessment has not been performed.

## SECTION 16: Other information

### Version history and indication of changes

Version	Revision date	Responsible	Changes
21.0.0	06-07-2016	GK	2, 9, 13, 14
22.0.0	25-10-2016	GK	9, 11

**Abbreviations:** DNEL: Derived No Effect Level. PNEC: Predicted No Effect Concentration.

# Safety Data Sheet

## Efadeck Clear 0454

Replaces date: 06-07-2016

Revision date: 25-10-2016

**References to literature and data sources:**

REACH: REGULATION OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals. DPD: Directive of the European Parliament and of the Council concerning the approximation of the laws, regulations and administrative provisions of the Member States relating to the classification, packaging and labelling of dangerous preparations. CLP: REGULATION OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL on classification, labelling and packaging of substances and mixtures.

**Other Information:**

The information in this Material Safety Data Sheet is based upon our knowledge and on European Union legislation. The user's working conditions are outside our control. It is the responsibility of the users to fulfil the requirements set by National Legislation. The information is no guarantee of the properties of the product. The Material Safety Data Sheet may only be reproduced with the permission of the manufacturer.

**Training advice:**

The instructions in this Material Safety Data Sheet are given on the assumption that the product is used as stated in item 1. Restrictions of use and special training requirements must also be complied with. The information in this Material Safety Data Sheet should be regarded as a description of the safety issues concerning the product.

**List of relevant H-statements**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

**Document language:** GB